HEMMET Photo Instructions



HEMMET instructions:

These are resin and metal bit kits. They require some cleaning before assembly

- Remove pieces from the sprues and clean all pieces
- You will need super glue to assemble these kits



Main HEMMET assembly



Parts for main HEMMET body



After cleaning

glue on

wheels.

stack to engine block



Add transmission and attach to main body and undercarriage box



Glue on mirrors to cab and then attach cab to main body assembly



Attach upright to back of engine assembly



You can have only the hatch, or full .50 cal coupla.





Base HEMMET assembly

Flatbed and Gun Truck Version

Flatbed and Gun Truck share many of the same pieces and assembly is the same for both.





Attach flaps to under carriage of flatbed/gun truck.



Attach control box to base of crane



Attach supports to base of crane



Flatbed/Gun

truck.

From the bottom, attach base of crane to back of flat bed. There is a slot for the crane base. Attach flaps as shown. Then glue to base model undercarriage from previous steps





Attach crane to base.



Finished flat bed should look like this







Finished Gun Truck should look like this

Use flatbed instructions for bed assembly

Add .50 cal support poles and guns

HEMMET Fueler version





Parts for Fuel truck.







Attach box behind engine compartment



Attach fuel back to main truck



Finished Fuel Truck should look like this

HEMMET Wrecker



Wrecker parts and base



Attach work area to base HEMMET



Attach flaps

to rear bed





Attach control box to rear bed





Attach jacks



Attach jacks to base HEMMET



Attach rear deck to base HEMMET



Attach crane to rear deck



Attach Tow bar support



Attach safety lights to rear deck and tow bar support





Attach tow bar assembly



Finished Wrecker should look like this